HD GAS PLUS SERIES

hotsy®

PRESSURE WASHERS / SINCE 1970

FEATURES

3 - 5 GPM @ 2700 to 4000 PSI
Recoil or electric-start gas engine models

COLD WATER | **GAS** | **DIRECT/BELT DRIVE**



HD 4.0/40 GeB (Belt)

Reliable **Honda GX** commercial-duty gasoline engines with 3-year warranty

50 ft. gray, non-marking hose includes guards couplers and swivels at both ends

Large flat free tires are puncture proof allow you to effortlessly navigate any terrain, from smooth pavement to rough job sites

Fatigue-free spring-loaded **trigger gun** with spray wand and side handle making for easy point-and-shoot cleaning action

Three, high-pressure **brass quick coupler nozzles**: 15°, 25°, 40° and a detergent nozzle

Low profile **handle** with cushioned grip is easy to push and pull

Integrated **wand, hose, and nozzle** storage

Durable VRT3 **unloader** with bypass loop diverts water flow when trigger gun is not activated

Models equipped with either a Hotsy, General Pump or AR **high-pressure pump**

Drain hose for pump & motor oil

Electric start models come with 12V Battery

Durable weld free, corrosion resistant **aluminum frame**

Vibration dampeners strategically placed to absorb vibration, preventing the unit from "walking" when in use

Modular design converts to skid



HD 4.0/40 G (Direct)

POWERED by HONDA

OPTIONS

PART NO.	DESCRIPTION
9.808-467.0	Trailer Kit (Fitting, Skid Feet, Low Pressure Hoses)
9.808-468.0	Skid Feet (Set of 4)
9.808-469.0	Hose Reel Direct Drive (bracket only)
9.808-470.0	Hose Reel Belt Drive (bracket only)
9.808-471.0	Self-retractable Hose Reel (incl. jumper hose & adaptors)
8.765-910.0	Injector Adjustable Hi-Draw 1.8 Acid Version (for HD3.0/27G)
8.765-911.0	Injector Adjustable Hi-Draw 2.1 Acid Version (HD3.5/35G, HD4.0/40G)
8.765-912.0	Injector Adjustable Hi-Draw 2.3 Acid Version (for HD5.0/30G)
8.783-040.0	Lance 40" Zinc-plated, handle and coupler
8.750-476.0	Hose Reel 50' Legacy
8.711-192.0	Hose Reel 50' A+
9.804-067.0	Hose Reel 100' A+

OPTIONS

PART NO.	DESCRIPTION
8.765-909.0	Injector 6' Vinyl Hose & Foot Valve Gray
4.760-846.0	Trigger Gun Classic G3/8
8.921-618.0	Non-marking Hose 3/8"x50' 4K Gray A+ SOXSW
8.925-129.0	Hose 3/8"x50' 1w TS SOXSW
8.925-229.0	Legacy Hose 3/8"x100' ID, 4500 PSI, 2-Wire, Smooth Cover, Black
8.753-572.0	A+ Surface Cleaner SC21
8.753-573.0	A+ Surface Cleaner SC24
9.302-242.0	Legacy Turbo Nozzle, 3.5/4350 PSI
9.302-243.0	Legacy Turbo Nozzle, 4.0/4350 PSI
9.302-247.0	Legacy Turbo Nozzle, 6.5/4350 PSI

HD GAS PLUS SERIES
Cold-Water Models

MODULAR PRESSURE WASHERS FOR HEAVY-DUTY CLEANING.

■ Honda Engines ■ 3 to 5 GPM @ 2700 to 4000 PSI ■ Compact/Modular Design

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	ELEC.START	PUMP MODEL	DRIVE	SHIP WT (LBS)
HD 3.0/27 G	1.107-503.0	3	2700	GX200	196	No	HOTSY LPP2535	Direct	145
HD 3.5/35 G	1.107-504.0	3.5	3500	GX270	270	No	HOTSY LPP3035	Direct	166
HD 4.0/40 G	1.107-505.0	4	4000	GX390	389	No	HOTSY LS4040	Direct	185
HD 4.0/40 Ge	1.107-506.0	4	4000	GX390 E/S	389	Yes	HOTSY LS4040	Direct	208
HD 3.0/27 G AR	1.107-513.0	3	2700	GX200	196	No	AR RCV3G27D-F7	Direct	180
HD 3.5/35 G AR	1.107-514.0	3.5	3500	GX270	270	No	AR RRV3G36D	Direct	213
HD 4.0/40 G AR	1.107-515.0	4	4000	GX390	389	No	AR RRV4G40HD-F24	Direct	228
HD 4.0/40 Ge AR	1.107-516.0	4	4000	GX390 E/S	389	Yes	AR RRV4G40HD-F24	Direct	251
HD 3.0/27 G GP	1.107-523.0	3	2700	GX200	196	No	GP EP1506G6	Direct	228
HD 3.5/35 G GP	1.107-524.0	3.5	3500	GX270	270	No	GP EP1309G8	Direct	251
HD 4.0/40 G GP	1.107-525.0	4	4000	GX390	389	No	GP EP1313G8	Direct	138
HD 4.0/40 Ge GP	1.107-526.0	4	4000	GX390 E/S	389	Yes	GP EP1313G8	Direct	166
HD 3.0/27 GB	1.107-507.0	3	2700	GX200	196	No	HOTSY LBP3030R	Belt	181
HD 3.5/35 GB	1.107-508.0	3.5	3500	GX270	270	No	HOTSY LPP3035G1	Belt	204
HD 4.0/40 GB	1.107-509.0	4	4000	GX390	389	No	HOTSY LM3840R.3	Belt	179
HD 4.0/40 GeB	1.107-510.0	4	4000	GX390 E/S	389	Yes	HOTSY LM3840R.3	Belt	208
HD 5.0/30 GB	1.107-511.0	5	3000	GX390	389	No	HOTSY LM4035R.3	Belt	223
HD 5.0/30 GeB	1.107-512.0	5	3000	GX390 E/S	389	Yes	HOTSY LM4035R.3	Belt	245
HD 3.0/27 GB AR	1.107-517.0	3	2700	GX200	196	No	AR RRA35G30N	Belt	223
HD 3.5/35 GB AR	1.107-518.0	3.5	3500	GX270	270	No	AR RRA4G40N	Belt	245
HD 4.0/40 GB AR	1.107-519.0	4	4000	GX390	389	No	AR RRA4G40N	Belt	143
HD 4.0/40 GeB AR	1.107-520.0	4	4000	GX390 E/S	389	Yes	AR RRA4G40N	Belt	164
HD 5.0/30 GB AR	1.107-521.0	5	3000	GX390	389	No	AR RRA55G30N	Belt	178
HD 5.0/30 GeB AR	1.107-522.0	5	3000	GX390 E/S	389	Yes	AR RRA55G30N	Belt	201
HD 3.0/27 GB GP	1.107-527.0	3	2700	GX200	196	No	GP EP1513S17	Belt	183
HD 3.5/35 GB GP	1.107-528.0	3.5	3500	GX270	270	No	GP ES2010S	Belt	212
HD 4.0/40 GB GP	1.107-529.0	4	4000	GX390	389	No	GP ES2010S	Belt	227
HD 4.0/40 GeB GP	1.107-530.0	4	4000	GX390 E/S	389	Yes	GP ES2010S	Belt	249
HD 5.0/30 GB GP	1.107-531.0	5	3000	GX390	389	No	GP ES2013S	Belt	227
HD 5.0/30 GeB GP	1.107-532.0	5	3000	GX390 E/S	389	Yes	GP ES2013S	Belt	249

WARNING: This product can expose you to chemicals including Lead and Diisononyl Phthalate, which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


Model Dimensions: 45.2 x 25.3 x 29.9
**Battery included on electric start models.*

DETERGENTS



To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE



Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tune-ups. Plus, we repair all brands.

hotsy®

NOTHING CLEANS LIKE A HOTSY!

EST. 1970

HOTSY.COM

Tel: 800.525.1976

Email: info@hotsy.com

Distributed by:

NorthBay EQUIPMENT SERVICE & SALES

(707)585-0100

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2025 Kärcher North America

P/N HOT_HDGPS Effective 01/25